

**DS-PR501-HWE**

Tri-X wireless receiver, compatible with AX Hybrid Pro control panel, used to expand wireless capability of the control panel. HIKVISION Tri-X detectors can be added to AX Hybrid Pro panel via this wireless receiver.

- 868MHz wireless receiver
- Wireless transmission distance up to 1600m
- Supports 32 wireless detectors, 8 wireless indoor sounders and 4 wireless outdoor sounders

## ▪ Specification

| Software features                               |                                                                    |
|-------------------------------------------------|--------------------------------------------------------------------|
| Compatibility list                              | DS-PK1-E-WE                                                        |
|                                                 | DS-PS1-I-WE                                                        |
|                                                 | DS-PS1-E-WE                                                        |
|                                                 | DS-PKF1-WE                                                         |
|                                                 | DS-PDP15P-EG2-WE                                                   |
|                                                 | DS-PDD12P-EG2-WE                                                   |
|                                                 | DS-PDMCS-EG2-WE                                                    |
|                                                 | DS-PDMC-EG2-WE                                                     |
|                                                 | DS-PDWL-E-WE                                                       |
|                                                 | DS-PDEB1-EG2-WE、DS-PDEB2-EG2-WE                                    |
|                                                 | DS-PDEB1-EG2-WE(B)                                                 |
|                                                 | DS-PDEB2-EG2-WE(B)                                                 |
|                                                 | DS-PDP15P-EG2-WE(B)                                                |
|                                                 | DS-PDP18-HM-WE                                                     |
|                                                 | DS-PDMC-EG2-WE(B)                                                  |
|                                                 | DS-PDMCK-EG2-WE(B)                                                 |
|                                                 | DS-PDBG8-EG2-WE                                                    |
|                                                 | DS-PDTPH-E-WE                                                      |
|                                                 | DS-PDCL12-EG2-WE                                                   |
|                                                 | DS-PDC10DM-EG2-WE                                                  |
|                                                 | DS-PDC10AM-EG2-WE                                                  |
|                                                 | DS-PDTP15AM-LM-WE                                                  |
|                                                 | DS-PDQP15AM-LM-WE                                                  |
|                                                 | DS-PDSMK-E-WE                                                      |
|                                                 | DS-PDHT-E-WE                                                       |
|                                                 | DS-PDCO-E-WE                                                       |
| Hardware features                               |                                                                    |
| Bus                                             | 1 input for control panel connection and 1 output for bus extender |
| Electrical characteristics                      |                                                                    |
| Typical voltage                                 | 12 VDC                                                             |
| Power supply                                    | 9-16VDC, up to 3A, provided by bus                                 |
| Power consumption                               | Quiescent Current      90 mA @12VDC                                |
|                                                 | Maximum Current      150 mA @12VDC                                 |
| Wireless transmission                           |                                                                    |
| RF frequency                                    | 868.0-868.6 MHz                                                    |
| Wireless technology                             | Tri-X Wireless Technology                                          |
| RF distance 改为 : Transmission Range(Free Space) | 1600m (Open area)                                                  |

## ▪ Available Model

DS-PR501-HWE

DS-PM643-WE(RU)



# See Far, Go Further



[www.hikvision.com](http://www.hikvision.com)  
[support@hikvision.com](mailto:support@hikvision.com)

